



We are Authorized Channel Partner



























### **ABOUT US**

We are pleased to introduce ourselves as a fast growing leading Industrial material supplier. Since 2016 based in Kolhapur with our vision "To be trusted and preferred industrial supplier to our client." We are dealing in power tools and accessories, Abrasives, Safety equipment's, Chemicals spray, Pneumatic tool and accessories, Construction anchors and chemicals etc.







### GENERAL PURPOSE SEALANT

B - 704

B-704 General Purpose IS Silicone Sealant is a one component, acid-curing, silicon sealant for general purpose sealing cures at room temperature in the presence of atmospheric moisture to give a permanently flexible silicon rubber. B-704 General Purpose IS Exhibits excellent primer less adhesion to most non-porous siliceous materials (e.g. glass, tiles, ceramics, enamel, glazed titles); impregnated, varnished or painted wood and some plastics.



### NEUTRAL SEALANT

B - 722

B-722 Neutral Universal Silicone Sealant is a Neutral cure, silicone sealant, exclusively created for weather sealing and glazing application. It forms highly resistive weatherproof seals on glass and exteriors. It's also suitable for sealing applications on surfaces where acetoxy silicone is not desired



### NEUTRAL SEALANT

B - 727

Neutral Silicone Sealant IS is a versatile and cost-effective single-component, neutral-cure sealant. It offers excellent sealing and bonding properties, making it ideal for interior and exterior applications. With its resistance to UV, moisture, and fungi, it is well-suited for sanitary joints, cold storage areas, and air conditioning sealing.



### GENERAL PURPOSE SEALANT

B - 779

B-779 Weather Silicone Sealant is a one-part, neutral-cure, architectural grade sealant. It easily extrudes in any weather and cures at ambient temp by reaction with moisture in the air to form a durable, flexible silicone rubber seal. Commonly used to apply on roof-tops & shades without any advance preparation.



### GENERAL PURPOSE SEALANT

B - 751

B-751 Acryfil PS is a highquality, plasto-elastic onecomponent joint sealant based on acrylic dispersions, Paintable Acrylic Sealant for Gaps & Cracks. Siliconised formulation, improve adhesion to full range of construction substrates



### NEUTRAL SEALANT

B - 794

B-794 FIXISIL HYB HT is a highquality, eco-friendly, onecomponent adhesive sealant based on MS Polymer Technology. With its exceptional tackiness and durability, it offers excellent adhesion to a wide range of materials. This neutral, elastic sealant is UV-resistant, water-resistant, and noncorrosive, making it suitable for both interior and exterior applications



### BONDZIL PU SEALANT

B - 711

B-711 Industrial Sealant is a strong, resilient polyurethane adhesive for bonding and sealing in various industries. It bonds a wide range of materials, offers chemical resistance, and is suitable for permanent elastic seals. Its applications include automotive, industrial, and construction sectors, with excellent resistance to aging and weathering.



### BONDZIL FLEXISIL SEALANT

B - 2160

B-2160 FIXISIL is suitable for various applications such as assembly bonding within the vehicle manufacturing. Suitable substrate materials are timber, metals, particularly aluminum, Sheet Metal, Metal primers and paint coatings, ceramic materials and plastics. Seek manufacturer's advice and perform tests on original substrates before using B-2160FIXISIL on materials prone to stress cracking. Test with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.



### BONDZIL FLEXISIL SEALANT

B - 2190

B-2190 M FIXISIL is designed for sealing joints in timber decking for boat, yacht and commercial ship constructions. This product is suitable for experienced professional users only. Test with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.





# SMALL ANGLE GRINDER 5"

### **ANGEL GRINDERS**





**GWS 600** 

### **LARGE ANGLE GRINDER 7"**



GWS 2200-180

#### SMALL ANGLE GRINDER 4"



**GWS 800** 

### LARGE ANGLE GRINDER 7"



GWS 24-180/230 JZ

### SMALL ANGLE GRINDER 5"



**GWS 14-125CI** 

### LARGE ANGLE GRINDER 9"



GWS 30-180/230 B



GWS 18-125L

### STRAIGHT GRINDER



**GGS 30 LS** 

### **HAMMER & DRILL**

### **ROTARY HAMMER**



Power Input 720 W Impact Energy 2.7 J, Drilling Capacity 22 mm, 1300 rpm, Impact Rate 4-200 bpm, Weight 2.2 Kg

IMPACT DRILL



Power Input 600 W, No-Load Speed 0-3000 rpm, Drilling Dia. in masonry wall 13 mm, Weight 1.7 Kg.

### **ROTARY HAMMER**



Power Input 800 W, Drilling Dia. in Concrete 4-26 mm, 4-26 mm, No-Load Speed 0-900 rpm, Single Impact Energy 0-3 J, Weight 2.7 Kg.

### IMPACT DRILL



Input Power 550 W, Rated Power Input 0-2800 rpm, Impact rate 0-41800 bpm, Drilling capacity in Concrete 13 mm, Drilling capacity steel/wood 10/25 mm

**GSB 550 KIT** 

### **DEMOLITION HAMMER**



Input Power 1100 W, Impact Rate 2900 bpm, Impact Energy 7.8 J, Tool Holder 17 Hex mm, Weight 5.5 Kg.

**GSH 500** 

### ROTARY DRILL



Power Input 550 W, No-Load Speed 0-630 rpm, Chuck Capacity- 13 mm, Drilling Dia. in Steel 16 mm, Weight 3 Kg.

**GBM 1600 RE** 

### **DEMOLITION HAMMER**



Power Input 1500 W, Impact Rate 900-1890 bpm, Impact Energy 16.8 J, Weight 10.1 Kg.

**GSH11E** 

### **ROTARY DRILL**



**GBM 50-2** 

Power Input 1200 W, No-Load Speed 1st Gear 250 rpm, 2nd Gear 100-510 rpm, Angular Cutter 50mm, Weight 14.7 Kg.

### **CUTTER & BLOWER**

### **CUT OFF SAW**



Power Input 2200 W, No-Load Speed 3800 rpm, Saw Blade Dia. 355 mm, Cutting Capacity Rectangle 0 100 x 196 mm, Cutting Capacity Square 0 119 x 119 mm, Cutting Capacity L-profile 0° 130 x 130 mm, Weight 14 Kg.

### **AIR BLOWER**

GBL 650



Power Input 650 W, No-Load Speed 16000 rpm, Weight Without Cable 1.4 Kg.. Volumetric Flow Rate 3.5 m/min, Standard Accessories 1 Nozzle

### **CUT OFF SAW**



Power Input 2400 W, No-Load Speed 3800 rpm, Cutting Capacity Rectangle 100 x 196 x 196 mm, Cutting Capacity Square 119 x 119 mm, Cutting Capacity Round 129 x 129 mm, Cutting Capacity L-Profile 130 x 130 mm, Weight 18.1 Kg.

### AIR BLOWER (HEAVY DUTY)



**GBL 82-270** 

Input Power 800 W, No-Load Speed 16000 rpm, Flow Rate 0-4.5 m3/s, Weight 1.8 Kg.

### BENCH GRINDER



**GBG 60-20** 

### **HEAT GUN**



Power Input 1800 W, Max Temperature 60/350/550°C., Air Flow Rate 350/350/550 rpm, Over-Heat Protection, Weight 0.75 Kg.

No Load Speed (50/60Hz) 3000/3600 rpm, Disc Dia. 200 mm,

Weight 17 Kg

### MARBLE CUTTER



No-Load Speed 12000 rpm, Tool Blade 4 inch, Cutting Depth (at 90°) 34 mm Net weight 2.5 Kg.

Rated Power Input 1200 W.

### **HEAT GUN**



Power Input 2000 W, Temperature Max 50-630°C. Adjustable Temp Steps, Air Flow rate 150/500 rpm. Infinitely Variable Airflow control-No Durability 500-750 h Weight 0.55 Kg.

**GHG 20-60** 





### **BOSCH**



### **WOOD WORKING TOOLS**

### **ORBIT SANDER 5"**



Sanding Pad Dia. 125 mm, No-Load Speed 7500-12000 rpm, Orbital Stroke Rate 15000-24000 rpm, Eccentricity 1.3 mm, Power Input 290 W, Weight 1.3 Kg.

### **GEX 125-1AE**



Power input 550 W ad speed 33000 rpm, Bit size 6/4 mm Weight 14 kg

**GKF 550** 

### **ORBIT SANDER 6"**



Sanding plate dia. 150 mm, No-load speed 4500-12000 rpm Orbital stroke rate 9000-24000apm, ower Input 340 W., Weight without cable 2.4 kg.

**GEX 34-150** 

### SABER SAW



**GSA 1300 PCE** 

### GST 90 BE

JIGSAW



Power input 710 W., Weight without cable 2.5 Kgs. Adjustable rebating depth 0-9mm No-load speed 16500 rpm,

Power input 650 W.

Power input 650 W.
No-load stroke rate
500-3100 spm
Weight
without cable 2.6 kg.
Cutting depth in
aluminium 20 mm.
Cutting depth in
non-alloyed steel 10 mm
ng depth in wood 85 mm.

**GHO 10-80** 



Power Input 1400W, No-load Speed 5200 rpm, Saw blade dia. 184mm, Cutting depth (90) 67mm. Cutting depth (45) 48mm. Veight without cable 4.1kgs

**GKS 190** 

### SCREW DRIVER



**GTB 650** 

Power input 650 W. Torque, (soft screw driving applications) 12 Nm. Tool holder 1/4" interna hexagon, No-load speed 0-5000 грт, Weight 1.4 Kgs

### **VACUUM CLEANER & HIGH PRESSURE WASHER**

### VACUUM CLEANER



Power input 1100 W. Vacuum Pressure 237 mbar, Max Air Flow 63 Motor I/sec., Dust Tank Capacity Gross 25 L. Tank Capacity Net Weight 6 Kg.

### HIGH PRESSURE WASHER



Maximum Pressure 125 bar, Maximum flow rate 360/h, Auto-stop, Motor type-Series, Power 1500 Watts, and 50hz, Hose length 5 m, Pump Type 3 Cylinder, Weight 6.8 kg.

**AQUATAK -125** 

### **VACUUM CLEANER**



Power input 1250 W. Vacuum Pressure 200 m bar Air Flow 63/sec. Motor, Dust Tank Capacity 25 L. Tank Capacity Net Weight 6.5 kg. **GAS 12-25** 

### HIGH PRESSURE WASHER



**AQUATAK -130** 

Maximum Pressure 130 bar, Maximum flow rate 380/h, Auto-stop, Motor type-Series, Power 1700 Watts, and 50hz, Hose length 6 m, Pump Type 3 Cylinder, Weight 7.8 kg.

### VACUUM CLEANER



GAS 35-L SMC+

Power input 1200 W, Max. Vacuum Pressure 254 M BAR Container Volume Gross 35L Weight 11.6 kgs



Maximum pressure 185 bar, Maximum flow rate 570 l/h, Hose length 10 m, Auto-stop. Weight 28.2 kgs. Motor power 2600 W. Integrated detergent Suction System, Handle Metal-Telescopic Handle with Hose Reel **GHP 5-75X** 

### **HIGH PRESSURE WASHER**



adjustment (flow) Weight 16.5 kg

### IMPACT WRENCH



Power input 920 W. speed 500/1300 rpm, Torque Max. 1000 nm, Bolt Dia. M30 Weight 7.3 kg.

**GDS 30** 

### **CORDLESS TOOLS**

### DRILL DRIVER



Battery voltage 12 V No-load speed (1/2) 0-400/0-1500 rpm, Torque (hard/soft) 30/14 Nm, Max. screw diameter 7 mm, Chuck size 10 mm Weight 0.97 kg.

### IMPACT WRENCH



Torque max. 285 Nm., No-load Speed 0-2800 rpm, Breakaway Torque , max. 500 Nm., Impact Rate 0-3600 bpm, Battery Voltage 18 V Weight 1.13 kg.

**GDX 18V-285** 

### DRILL DRIVER



Torque, max. (hard/soft) 50/21 Nm. No-load speed 0-500/0-1900 rpm, Head Lenght 162 mm Battery voltage 18V..

**GSR 185 - LI KIT** 

### IMPACT WRENCH



Battery voltage 18 V Torque max 1600 Nm No-load speed 0-800/ 1300/ 1750 rpm, Square drive 3/4 inch. Screw Dia. M16-M33,

**GDS 18V-1600 HC** 

### IMPACT DRILL



Torque, max.-350 Nm
Tool holder-1/2" square
No-load speed (3rd
No-load speed-0-1,200 rpm
Torque adjustment range,
min./max., 1st level-0/85 Nm
2nd level-0/200 Nm
3rd level-0/350 Nm
Weight excl. battery-1.1 kg
Impact rate (1st level)-0-1,800 bpm
(2nd level)-0-2,600 bpm
(3rd level)-0-3,400 bpm

**GDS 18V - 350** 

### IMPACT SHUTOFF



Battery Voltage 4.0 Ah, No-load speed 0-2500 rpm, Auto shutoff Torque 30-140 Nm. Max. Torque 300 Nm., Max. Bolt Size M18 Weight 1.2 kg.

IDS 18V- 200

### IMPACT WRENCH



No-load speed 0-2500 rpm, Torque, max. 400 rpm, Battery voltage 18 V. Tool holder-1/2" external square Screw dia. M6 - M16 Weight incl. battery 1.85 kg.

**GDS 18 V-400** 

### **BATTERY & CHARGER**



**GBA/GAL 18** 





## **BOSCH**

### **HAND TOOLS**











COMBINATION PLIERS 180 MM

LONG-NOSE PLIERS 180 MM

DIAGONAL SIDE CUTTER 160 MM

CARPENTERS' PINCERS 200 MM

SCREWDRIVER SET 6-PIECES



Scope Of Supply
1 x Drive Socket 1/4" 10 x
Sockets: 5.0, 5.6.0, 7.0,
8.0, 9.0, 10.0, 11.0, 12.0,
13.0 mm 1 x Universal
Screwdriver 18 x Bits: PH
1/2/3, PZ 1/2/3, SL 4/5/6,
TX 10/15/20/25/30, H
3/4/5/6 1 x Universal
Adapter 1 x Extension
adapter: 50 mm 2 x
Adapter: Hex 1/4" and 1/4"
Hex 1 x Carrying case Hex 1 x Carrying case

Scope Of Supply 1 x 1/2" Ratchet 24 x 1/2" Drive accessories 1 x Storage case



Scope Of Supply 9 x Hex Keys (Sizes: 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10) 1 x Organizer



Scope Of Supply 15 x Wrenches: 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21 1 x Organizer



1/4" DRIVE SOCKET SET 34-**PIECES** 









COMBINATION WRENCH SET

15-PIECES

Scope Of Supply
1 x Flat steel file
1 x Half round steel file
1 x Round steel file
1 x Square steel file
1 x Triangle steel file

CLAW HAMMER 340 G/12 OZ

**CLUB HAMMER 1000 G** 

Material Carbon Steel (#55CS) Handle Core Fiberglass Standards ISO 15601; DIN 1193





HACKSAW 300 MM

FILE SET 200 MM 5-PIECES



**SNAP OFF KNIFE** 



ADVANCED HAND **TOOL SET 64-PIECES** 



ADVANCED HAND **TOOL SET 132-PIECES** 



WIRE STRIPPER



**WATER PUMP PLIERS** 







RATCHET SPANNER SETS10 PCS

**LEVELS 60 & 120 CM** 

VDE SCREWDRIVERS SET SL/PH 7 PCS

**VOLTAGE TESTER SL 3** 





VDE CRIMPING PLIER 180 MM



VDE UNIVERSAL WIRE STRIPPER 160 MM



VDE CABLE SHEAR 200 MM



VDE PLIER SET 4 PCS



VDE SPANNER SET 4 PCS



Fast-acting repair system, ideal for installers and

workshops in the metal processing sector.High-quality two-component reaction resin system. After hardening, can easily be processed





### **CHEMICAL**



Outstanding long-term protection and optimum metal surface appearance. Zinc colour, Matt effect. High degree of resistance to running. Protection against corrosion (500 hours).

### (500 hours)

ZINC SPRAY



Lithium-soap graphite grease. Resistant to high pressure due to EP additives. Excellent emergency running properties. Good sealing action and protection against corrosion.

**MULTI-PURPOSE GREASE II** 



### For cleaning and degreasing during maintenance and repair work. Fast flashroff behavior and excellent cleaning performance

### **BREAK CLEANER**



Film protects battery terminals, pole terminals and plug connections from corrosion, weather and battery acids. Prevents transfer resistances and voltage drops. Longer battery life.



Environmental friendly cleaning agent for workshops, machinery and vehicles.

High-quality pin impact mechanism in oil bath

Operating Torque: (350-1440) Nm.

with 6-disc motor.. 4 stage torque control.

High quality rust releaser. High capillary activity. Optimum corrosion protection. Excellent water displacement. 300 g & 100ml

**RUST OFF** 

**BMF CLEANER** 

**BATTERY TERMINAL PROJECTOR** 



**METAL FE 1** 

**WIRE ROPE SPRAY** 

### PNEUMATIC TOOLS

**IMPACT WRENCH** 

### IMPACT WRENCH



Powerful 0.85hp (640W) Powerful 0.85hp (640w) high performance motor for fast, efficient grinding in tight quarters. Bevel gearing in angle head provides extended life and smooth low vibration

Extremely robust, powerful chisel hammer with Max.

**DWS-125** 



DSS 1"

### CHISEL HAMMER

ANGLE GRINDER



**DMH 10** 

### **BELT SANDER**



Tool with high removal capacity, ideal for sanding, removes burrs and rust. Adjustable arm up to 360° Arm Holder with integrated spring that keeps tension on the sanding belt. Quick and DBS 20 easy replacement of sanding belt

cold hands. Precision planetary

# screwdriver with speed regulation and plastic handle to protect against vibrations and

RATCHET

IMPACT WRENCH

**DRH 1/2**"

DSS 3/4"

### ORBIT SANDER

reverse.

Outstanding power-to-weight ratio. High perform system provide Six-positionce twin hammer impact

mechanism and heavy duty hammer a to 860 Nm

management operated by turn-knob in forward & reverse.

of maximum torque in



D 150 MM

DSS 1/2"

# gear. Max. torque: 70 Nm. Right/left changeover switch recessed.

Durable ratchet

### **INDUSTRIAL PNEUMATIC TOOLS**



### PE 5800-B

PE 4200 L

Blows per min-4200, Aprox.Weight-2KG Air InletNPTE-RC 1/2"



**PE 800** 

PE 21000



PE 35000

Free Speed 35000 rpm, pindleThread Size-M 10, CollectCapacity-6MM, Approx. Weight 0.6KG, AirInletNPTF-RC 1/4"



**PE 850** 





PE 75 H



Free Speed 21000 rpm,

SpindleThread Size-M 10, CollectCapacity-6MM, Approx. Weight 2.8KG, AirInletNPTF-RC 3/8"







### **DIE GRINDER**



STRAIGHT DIE GRINDER DGS 31



RIGHT ANGLE DIE GRINDER

**DGR 31** 



4" ANGLE GRINDER 1.3 HP

52630

### ANGLE GRINDER



5" ANGLE GRINDER 1.3 HP

52633



7" ANGLE GRINDER 2.0 HP

50348

### **ORBITAL SANDER**



0.5HP OFFSET DIE GRINDER

52218



3" (89MM) ORBITAL SANDER

59015



6"/5" ORBITAL SANDER SUPREME

56830



6"/5" ORBITAL SANDER EXTREME

X61HS



6"/5" ORBITAL SANDER RED SPIRIT

59025

### **BELT SANDER**



**BELT SANDER 18"** 

40320

### SPREY



SPREY GUN 1.2 TO 1.4 NOZZLE

SATA JET 1000 IC

### ABRESSIVE



VELCRO DISC 6" & 5"

DYNABRADE



VELCRO PAD
DYNABRADE




PAPER DRY ROLLS
DYNACUT GOLD

# RATCHET ADJUSTABLE-DUAL SCALE TT120, 4", 4-20 N-m, 35-180 lbf-in



13830 TT120, 4", 4-20 N-m, 35-180 lbf-In				
	13831	TT120, ", 4-20 N-m, 35-180 lbf-In		
	13841	TT150, ", 10-50 N-m, 8-35 lbf-In		
	13842	TT150, 1/2", 10-50 N-m, 8-35 lbf-In		
		RATCHET ADJUSTABLE-DUAL SCALE		
	130101	Model 60, 1/2", 12-60 N-m, 10-45 lbf-ft		
	130103	Model 100, 1/2", 20-100 N-m, 20-80 lbf-ft		
	130104	Model 200, 1/2", 40-200 N-m, 30-150 lbf-ft		
	130105	Model 300, 1 1/2", 60-300 N-m, 45-220 lbf-ft		
130106 M		Model 340, 1/2", 60-340 N-m, 45-250 lbf-ft		
	RATCHET ADJUSTABLE-DUAL SCALE			
	14037	Pro 650, 3/4", 130-650 N-m, 100-480 lbf-ft		
	14015	Pro 800, 3 1/2", 200-800 N-m, 150-600 lbf-ft		
	14016	Pro 800, 1", 200-800 N-m, 150-600 lbf-ft		
	14002	Pro 1000, 1/4", 300-1,000 N-m, 220-750 lbf-ft		
	14003	Pro 1000, 1", 300-1,000 N-m, 220-750 lbf-ft		
	14004	Pro 1500, %", 500-1,500 N-m, 370-1,100 lbf-ft		









Female Torque Handle



nale Torque Handle 16 mm Spigot End





### **ABRESSIVES**









SANDING BELT 20 × 520



XZ 677



SANDING BELT 50 × 2000



XZ 677/ PZ 628



**VA A113** 



**KA 169** 

# **APIDOR**

### **DEPRESSED CENTRE WHEELS**



DIAMETER (D) MM	THICKNESS (T) MM	BORE (H)	UNIT PACK Nos.
63/80 mm	2.5 to 6.0 mm	9.53/12.7 mm	50
100 mm	3 to7 mm	16 mm	50
115 mm	3 to7 mm	22.23 mm	40
125 mm	3 to7 mm	22.23 mm	40
230 mm	3 to7 mm	22.23 mm	25
180 mm	3 to7 mm	22.23 mm	15

These are normally reinforced with 2% or 3 liber glass reinforcements & are normally used on portable angle grinder m/cs.

**APPLICATION:** These are widely used for grinding of weld bed cleaning metal surface, cutting-off gates, risers & linishing surfaces in Foundries, Welding shops, Steel mills, Metal fabrications plants. Ship yards, Pipeline Industries etc.

**PRODUCT RANGE:** For the best results APIDOR gives you wide range of products to suit different applications. These wheels are normally used at an angle  $15^{\circ}$  to 30' with the work piece or may be used at right angle to the work piece.

This are fiber glass reinforced cutting wheels and should be mounted on fixed or portable machines designed to run at 80m/s to 100m/s. These products adhere to **EN 12413 normss of safety** 

Apidor manufactures reinforced products with the following construction.

R1- Reinforced on one side or in the center. R3-Triple reinforced

### REINFORCED CUT-OFF WHEELS

DIAMETER (D) MM	THICKNESS (T)	BORE (H)	UNIT PACK Nos.
25-125 mm	2 to 6.0 mm	6-22.23 mm	50
150-180 mm	2 to 6.0 mm	12.7-22.23 mm	40
180 mm	2 to 6.0 mm	15.88 & 22.23	25
200-230 mm	2 to 6.0 mm	22.23 mm	25
230 mm	2 to 6.0 mm	22.23 mm	15
300-350 mm	2.5-6.0 mm	25.4 mm	25
400-450 mm	3-6.0 mm	25.4-50.8 mm	20
500 mm	3.5-6.0 mm	25.4-80 mm	15
600-650 mm	5-10 mm	8-25 mm	As Per Order
700-810 mm	5-10 mm	6-12 mm	As Per Order

WHEEL BRAND	MATERIAL REMOVAL RATE	GRINDING RATIO	RECOMMENDED FOR
HIFY	MEDIUM	MEDIUM	General Steel, Fabrication, Pipes Fabrication, Ship Yards, Welding shops
FYTER	HIGH	LOW	
ZEN SUPER	HIGH	MEDIUM	
SUPER FAST	HIGH	MEDIUM	
METAFLEX	MEDIUM	MEDIUM	
ZENGOLD	MEDIUM	HIGH	
ULTRA	MEDIUM	HIGH LOW	
FAST CUT	MEDIUM	LOW MEDIUM	









### **TECMEN PAPR**

Application:

For welding purpose



### **SCABA**

(Self Contained Breathing Apparatus)

Emergency rescue / respond device Advanced Backplate, Digital Pressure Gauge & Cylinder



### **COMPLETE AIRLINE SET**

- Application: Welding, Sand Blasting, Powder coating, Buffing, Painting, Cutting, Drilling
- Paint: Paint spray, Mixing
- Pharmaceuticals: Bulk drugs, material handling



### CLEANAIR BASIC & EVO PAPR

Application:

- Industrial Grinding, Surface finishing operations etc.
- Dusty industrial environments Material handling
- Automotive & shipbuilding industry
- Painting & weldingCement, Bagging
- Food industry, Processing

### **SAFETY GOOGLES**











E 101

E 102

E 305

E 503

E 507











E 603

E 750

**EARMUFF N 555** 

N 101

N 303

### **DUST MASK**



CLASS: FFP1 S Protection: Solid Dust / Mist M.U.L: Upto 4 x OEL V Style



CLASS: FFP1 SL NRD CE Protection: Solid Dust / Mist M.U.L: Upto 4 x OEL Exhalation Vent Valve



CLASS: FFP2 NR D CE
Protection: Solid Dust/Mist/ Nuisance Leve
of Organic Vapour
M.U.L: Upto 12 x OEL Exhalation Vent Valve
Activated Carbon Layer

414 SLOV - V



CLASS: FFP2 NR D CE Protection: Solid Dust / Mist/ Nuisance Level of Organic Vapour/ Gases below > TLV Exhalation Vent Valve M.U.L: Upto 12 x OEL Activated Carbon

425 SLOV - V



CLASS: FFP2 NR D CE Protection: Solid Dust / Mist 37/101 M.U.L: Upto 12 x OEL Exhalation Vent Valve

V 420 SLV

V 410 V



V 44+

CLASS: FFP3 NR D CE M.U.L: Upto 50x OEL Protection: Solid Dust / Mist Inside Clip & Nose Liner Exhalation Vent Valve

CLASS: FFP2 S
Protection: Solid Dust / Mist
M.U.L: Upto 12 x OE



CLASS: N95 TC-84A-8126 Protection: Non oil based particles



"3 Ply" Style Surgical Ear-loop / Tie Approved Class 1, 2, 3 available. (Bacteria Filtering efficiency) of 98%



CLASS: FFP2 5 45/101 Protection: Solid Dust / Mist M.U.L: Upto 12 x OEL Exhalation Valve Vent Half Foam Seal

V 430 SLV

V 90 V

V 4400 N 95

V 1010

**V 20V** 









HALF FACE MASK

HALF FACE MASK



HALF FACE MASK



**FULL FACE MASK** 



HELMET













**FACE SHIELD** 

FC 58



**FACE SHIELD** 

FC 38 B



**HELMET** 

Н 3000



HELMET

H 2000



HELMET

H 4000

### **HAND GLOVES**





Construction: Knitted Linner Material: Polyester Coating Material: Nitrile Finishing: Palm Coating Guage: 13 Cuff Style: Knit Wrist Size: 6,7,8,9,10 Length (mm): 210-255

GENERAL PURPOSE

#### Standard & Certification: EN 388:2016 +A1.2018 : 4131A



Construction: U3 Knitted Linner Material: Polyester Coating Material: Nitrile Finishing: Palm Coating Guage: 13 Cuff Style: Knit Wrist Size: 6,7,8,9,10 Length (mm): 210-255

GENERAL PURPOSE
GRIPPER

#### Standard & Certification: EN 388:2016 +A1.2018: 2142A



Construction: Knitted Linner Material: Polycotton Coating Material: Natural Rubber Latex Finishing: Palm Coating Guage: 10 Cuff Style: Knit Wrist Size: 7,8,9,10 Length (mm): 210-255

**GENERAL PURPOSE** 

#### Standard & Certification: EN 388:2016 +A1.2018 : 4344D



Construction: Knitted Linner Material: HPPE, Glass Fiber, Spandex, Nylon Coating Material: Nitrile Finishing: Palm Coating Guage: 13 Cuff Style: Knit Wrist Size: 6,7,8,7) Length (mm): 215-250

CUT PROTECTION

NSC - 05

### Standard & Certification: EN 388:2016 +A1.2018 : 4444E



Class 0 to Class 4

Construction: Knitted Linner Material: HPPE, Glass Fiber, Spandex, Nylon Coating Material: Nitrile Foam Finishing: Palm Coating Guage: 13 Cuff Style: Knit Wrist Size: 6:7,8,9,10 Length (mm): 200-250

CUT PROTECTION

### NFC - 05

### NITRO PRO

### Standard & Certification: EN 388:2016 +A1.2018 : 3121 X



Construction: Knitted
Linner Material: Polycotton
Coating Material: Natural
Rubber Latex
Finishing: Palm Coating
Guage: 10
Cuff Style: Knit Wrist
Size: 7,8,9,10
Length (mm): 210-255

Construction: Knitted

GENERAL PURPOSE

### **PU PRO**

### EN 388:2016 +A1.2018 : 4344D Construction: Knii inner Material: HPPE, G Fiber. Soandex. N

Standard & Certification:



Construction: Knitted Linner Material: HPPE, Glass Fiber, Spandex, Nylon Coating Material: Natural Rubber Latex Finishing: Palm Coating Guage: 13 Cuff Style: Knit Wrist Size: 7, 8, 9,10 Length (mm): 210-255

CUT PROTECTION

### PLC 05

### GRIPSTER

#### Standard & Certification: EN 388:2016 +A1.2018 : 4121A EN 374:2003: AJK



Linner Material: HPPE, Glass Fiber, Polyster Coating Material: Polyurethane Finishing: Palm Coating Guage: 13 Cuff Style: Knit Wrist Size: 7, 8,9,10 Length (mm): 210-255

**CUT PROTECTION** 

### PU PRO 05

#### Standard & Certification: EN 388:2016 +A1.2018 : 4121A EN 374:2003: AJK



Linner Material: Interlock Cotton Coating Material: Nitrile Grip Design: Diamond Cuff Style: Straight Size: 8,9,10 Length (mm): 350

### **CHEMICAL PROTECTION**

### PROCHEM



**ELECTRICAL GLOVES** 



**SAFETY GLOVES** 

ALUMINIZED



SLEEVES

MAXICUT ULTRA



Certification: EN 388:2016 +A1.2018 : 4344D

Standard &

**FULL ARMID GLOVES** 

**FULL ARMID GLOVES** 



**ELECTRICAL LOTO KIT** 

ELECTRICAL



MECHANICAL LOTO KIT

MECHANICAL









**SAFETY SHOES** 

**BOXER** 

**5** 

**SAFETY SHOES** 

LITE



**SAFETY SHOES MF 2020** 



**SAFETY SHOES** LITE



**B.K.AK** 



**SAFETY SHOES** 

**SAFETY SHOES** 



**SAFETY SHOES** 



**SAFETY SHOES** 

**VAULTEX AKON 63** 



SAFETY SHOES

**VAULTEX ICON** 

**VAULTEX EPIC 051** 

*UDYOGI* 

LIFE IS PRECIOUS

**VAULTEX PVC (SWIFT)** 





**ALUMINIZED SUIT** 

**APRON** 



**ALUMINIZED APRON** 

**APRON** 



**ACE FLASH SUIT APRON** 



**EYE SHOWER** 



**SAFETY SHOWER** 



**SAFETY SHOWER HAWS** 

**PVC-7890** 



**PORTABLE SHOWER** 

EW-3501



**EYE SHOWER** 

EW 500









**SAFETY HARNESS UB 102** 

**FALL ARRESTER UB 2011** 




**FALL ARRESTER UB 2010** 

**SAFETY HARNESS** ECO-1





**SAFETY HARNESS** 



**SAFETY NET** 

**PLASTIC** 



**FIRST AID BOX** 

**PLASTIC** 



REFLECTIVE JACKET

**JACKET** 



**PAINTING APRON** 

**DUPONT TYVEK SUIT** 



TYCHEM-C





### **KOLHAPUR**

Gat No. 123, Shiye Phata, MIDC Shiroli, Tal. Hatkanangale, Dist. Kolhapur - 416122



www.unityindiaa.com

# **PUNE**

Shop No. 2, Opp. Madhuban 0 Trade Steel, Jotiba Nagar, Talawade Road, Pune - 411062

sales@unityindiaa.com



+91 96894 76847

+91 99222 43770